

TECHNICAL DATA SHEET



Doc. Nr. TDS_5-500

Version: 2016_01

2K FLOORCOAT HIGH GLOSS 2:1 5-500

Eurolux 2K Floorcoat High Gloss 5-500 is a two-component, polyurethane based finishing coat for inside and outside concrete floors. Excellent for basement floors, garage floors, decks, etc. Quick drying, easy to use. Water and oil resistant. Surface should be dry and clean. For interior and exterior use.

To increase grit, it is recommended to add polymer grit additives.

Colours: available in wide industrial colour range.

Only for professional use.



Mixing ratio (by volume), at 20°C

**100% 2K Floorcoat High Gloss 5-500
50% 2K Hardener 2-200
0 - 5% 2K Thinner 3-50**

Potlife

Ca. 2 hr



**Sprayviscosity,
DIN 4, at 20°C**

-



Application method

**By roller or brush
Apply in a well-ventilated place
Use a protective face-mask**



Number of coats

1 - 2 ; Film thickness 40 – 60 µm



Flash off at 20°C

10 – 15 min



**Drying time at
20°C:**

overnight

Theoretical coverage

7 – 10 m²/l depending on the absorbence of the surface

Storage

Keep away from sources of ignition. Store separately from flammable substances. Keep container tightly closed in a dry, cool and well ventilated place. Storage temperature above 3°C.

Shelf-life

2 years

The in this leaflet supplied details and advises are based on our experiences and best knowledge. The user will be deemed to have satisfied himself independently of the suitability of the product for his own particular purpose. Guarantees cannot be claimed from this leaflet.