

TECHNICAL DATA SHEET







Doc. Nr. TDS_6-850

Version: 2018_01

ANTIGRAVEL HS 6-850

Eurolux 6-850 Antigravel HS is designed for protection of car bodies, based on synthetic resins. It forms an elastic, fine-grained texture that is resistant to stone chipping. It protects thresholds, wheel arches, spoilers and other elements of the car body against stone impact, water, snow, salt and oils. Provides a good protection against corrosion. Good adhesion to steel, galvanized steel, aluminium, polyester putties, epoxy primers, acrylic primers, plastics. It also has strong silencing properties. After drying it can be coated with any type of topcoats. Only for professional use.

Preparation	Before applying shake the container with antigravel about 3 minutes. Break off screw cap protection and attach the spraygun directly to the container.
 Application method	Apply with a spraygun for thick masses, with nozzle diameter 4 mm at the airpressure 2 – 4 bar from a distance of approximately 15 – 20 cm.
 Number of spraycoats	1 – 2 ; Film thickness 100 µm
 Flash off at 20°C	10 - 15 min.
 Drying time at 20°C:	The surface can be recoated by another product after 3 -4 hours
VOC-regulation	VOC-compliant. The maximum VOC content for ready to use product is: <840 g/l.
Storage	Keep away from sources of ignition. Store separately from flammable substances. Keep container tightly closed in a dry and well ventilated place. Storage temperature above 3°C.
Shelf-life	2 years

The in this leaflet supplied details and advises are based on our experiences and best knowledge. The user will be deemed to have satisfied himself independently of the suitability of the product for his own particular purpose. Guarantees cannot be claimed from this leaflet.