

TECHNICAL DATA SHEET









Doc. Nr. TDS_1-950

Version: 2022_01

2K UHS MIRROR-LOOK CLEARCOAT 1-950

Eurolux 2K UHS Mirror-look Clearcoat 1-950 is a Top Quality Clearcoat for the highest demanding refinish projects. Outstanding wet-look appearance with a deep rich gloss. Superior gloss retention. Non-yellowing, high durability and excellent chemical and mechanical properties. Ultra High Solid content. Strong UV-protection. Fast curing times. Air drying and forced drying. Provides a long-term surface protection and has excellent adhesion on solvent borne and water borne basecoats. Suitable for car and truck repair. Only for professional use.

	Mixing ratio (by volume), at 20°C	100% 2K UHS Clearcoat 1-950 50% 2K UHS Hardener 2-950 0 – 5% 2K AC Thinner 3-50
	Potlife	1 hr
	Sprayviscosity, DIN 4, at 20°C	17 – 20 s
	Application method	1,3 – 1,4 mm 2,0 – 2,5 bar
	Number of spraycoats	1,5 - 2 ; Film thickness 40 – 60 µm
	Flash off at 20°C	5 min
	Drying time at 20°C: 60°C:	4 hr 20 min
	Theoretical Coverage	12 m²/l (50 µm dry film thickness)
	VOC-regulation	VOC-compliant 2004/42/IIIB(d)(420)<420
	Storage	Keep away from sources of ignition. Store separately from flammable substances. Keep container tightly closed in a dry and well ventilated place. Storage temperature above 3°C.
	Shelf-life	4 years

The in this leaflet supplied details and advises are based on our experiences and best knowledge. The user will be deemed to have satisfied himself independently of the suitability of the product for his own particular purpose. Guarantees cannot be claimed from this leaflet.